

## TR 117 - Teknik Özellikler



### Description

TR 117 ilaçlama ve sulama makineleri ile sulama uygulamaları için idealdir. Özel olarak tasarlanmış sırt deseni mükemmel çekiş ve olağanüstü kendi kendini temizleme özellikleri sağlar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: İlaçlama ve sulama makinesi

Version	STANDARD
Type	TT
Tyre Size	11.2 - 24
LI/SS	106 A8

Dimensions US Standard

Usa code	94028368
Ply Rating	6
Section Width (inch)	11.2
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	20
Rolling Circumference (inch)	126.2
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-001967
TRA Code	R1

Load capacity (lbs)

mph / psi	26	34
25	2090	---
CREEP	---	4420

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN )

Printed on 5/3/2024 7:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..