

TR 126 - Teknik Özellikler



Description

TF 126, toprak işleme operasyonlarında kullanılan küçük traktörlere uymak üzere tasarlanmıştır. Derin dişler ve sırt deseni mükemmel çekiş sağlar ve tüm çalışma koşullarında en iyi lastik performansını sağlayan üstün yük kapasitesi özelliklerine sahiptir.

UM

US Standard

Construction



Machinery

Zirai: Küçük Traktör

Version	HD
Туре	π
Tyre Size	6 - 14
II/SS	77 A8

Dimensions US Standard

Usa code	94069972
Ply Rating	8
Section Width (inch)	6.2
Overall Diameter (inch)	25.8
Static Loaded Radius (inch)	12
Rolling Circumference (inch)	77.9
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-007418
TRA Code	R1

Load capacity (lbs)

mph / psi	56
25	990

Printed on 4/25/2024 4:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..