

TR 128 - Teknik Özellikler



Description

TR 128, hizmet tipi traktörler ve rototillerler için özel olarak tasarlanmıştır. Geniş ve derin diş tasarımı ve özel kesilme ve kopmaya karşı dirençli hamur, uzun lastik ömrü sunar. TR 128 ıslak zeminde maksimum çekişe sahiptir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Rototiller • Genel kullanım aracı

Version	STANDARD
Type	TT
Tyre Size	5 - 12
LI/SS	64 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	127
Overall Diameter (mm)	554
Static Loaded Radius (mm)	262
Rolling Circumference (mm)	1700
Rim Rec	4 JA
ECE	E11-106R-005189

Load capacity (Kg)

km/h / bar	3.50
30	280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 3:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..