

TR 133 - Teknik Özellikler



Description

TR 133, toprak işleme uygulamalarında kullanılan traktörler için özel olarak tasarlanmıştır. Daha yüksek diş sayısı sayesinde bu lastik, mükemmel çekiş ve kendi kendini temizleme özelliklerine sahiptir. TR 133, daha uzun lastik kullanım ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38 (14.00 - 38)
LI/SS	136 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	350
Overall Diameter (mm)	1580
Static Loaded Radius (mm)	735
Rolling Circumference (mm)	4843
SRI (mm)	750
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003549
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	2240

Printed on 3/4/2024 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..