

TR 133 - Teknik Özellikler



Description

TR 133, toprak işleme uygulamalarında kullanılan traktörler için özel olarak tasarlanmıştır. Daha yüksek diş sayısı sayesinde bu lastik, mükemmel çekiş ve kendi kendini temizleme özelliklerine sahiptir. TR 133, daha uzun lastik kullanım ömrü sağlar.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38 (14.00 - 38)
LI/SS	132 A8

Dimensions US Standard

Usa code	94043897
Ply Rating	10
Section Width (inch)	13.8
Overall Diameter (inch)	62.2
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	190.7
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003549
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	4410

Printed on 4/26/2024 8:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..