

TR 135 - Teknik Özellikler



Description

TR 135 toprak işleme uygulamalarında kullanılan traktörler için en uygun lastiktir. Güçlendirilmiş gövdesi ve özel kesilme ve kopmaya karşı dirençli hamur, uzun bir lastik kullanım ömrü sağlar. Çekiş, kendi kendini temizleme özellikleri ve yük kapasitesi, TR 135 lastiği en zorlu zemin koşullarında bile ideal bir ortak kılan temel özelliklerdir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Traktör
Endüstriyel: Römork

| | |
|-----------|-----------|
| Version | HD |
| Type | TL |
| Tyre Size | 12.4 - 24 |
| LI/SS | 121 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 8 |
| Section Width (mm) | 315 |
| Overall Diameter (mm) | 1160 |
| Static Loaded Radius (mm) | 531 |
| Rolling Circumference (mm) | 3477 |
| SRI (mm) | 550 |
| Rim Rec | W 11 |
| Rim Alt | W 9 ; W 10 |
| ECE | E11-106R-002959 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 2.30 |
|------------|------|
| 30 | 1450 |

Printed on 2/23/2024 10:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..