

## TR 135 - Teknik Özellikler



### Description

TR 135 toprak işleme uygulamalarında kullanılan traktörler için en uygun lastiktir. Güçlendirilmiş gövdesi ve özel kesilme ve kopmaya karşı dirençli hamur, uzun bir lastik kullanım ömrü sağlar. Çekiş, kendi kendini temizleme özellikleri ve yük kapasitesi, TR 135 lastiği en zorlu zemin koşullarında bile ideal bir ortak kılan temel özelliklerdir.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Traktör  
Endüstriyel: Römork

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	137 A6

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	345
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	606
Rolling Circumference (mm)	3908
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-002818
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.50
30	2300

Printed on 4/25/2024 6:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..