

TR 136 - Teknik Özellikler



Description

TR 136, BKT tarafından, toprak işleme ve taşıma operasyonlarında kullanılan traktör ve römorkların donatılması için geliştirilmiştir. Bu lastik, makinenin çalışmada süresini azaltıp üretkenliğinizi artırmak için üstün kesilme ve kopma direncinin yanı sıra tüm çalışma koşullarında daha iyi çekiş sağlar. Daha yüksek diş sayısı sayesinde TR 136, yüksek yüklerde bile üstün çekiş sağlar.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Traktör • Römork

Version	SPECIAL
Type	TT
Tyre Size	18.4 - 30
LI/SS	145 A8

Dimensions US Standard

Usa code	94004300
Ply Rating	12
Section Width (inch)	18.4
Overall Diameter (inch)	61
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	185.8
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-004436
TRA Code	R1

Load capacity (lbs)

	mph / psi	32
	25	6400

Printed on 12/10/2023 9:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..