

## TR 136 - Veri Sayfasını İndir



### Description

TR 136, BKT tarafından, toprak işleme ve taşıma operasyonlarında kullanılan traktör ve römorkların donatılması için geliştirilmiştir. Bu lastik, makinenin çalışmada süresini azaltıp üretkenliğinizi artırmak için üstün kesilme ve kopma direncinin yanı sıra tüm çalışma koşullarında daha iyi çekiş sağlar. Daha yüksek diş sayısı sayesinde TR 136, yüksek yüklerde bile üstün çekiş sağlar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Traktör • Römork

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18.4 - 26	SPECIAL	94039906	R1	142 A8	12	W 16 L	W 15 L	18.9	57.1	25.4	165.6	TL	E11-106R-003614
18.4 - 26	STANDARD	94046294	R1	146 A8	14	W 16 L	W 15 L	18.9	57.1	25.4	165.6	TL	E4-106R-002301
18.4 - 26	STANDARD	94004218	R1	142 A8	12	W 16 L	W 15 L	18.9	57.1	25.4	165.6	TL	
18.4 - 26	STANDARD	94026265	R1	142 A8	12	W 16 L	W 15 L	18.9	57.1	25.4	165.6	TT	E4-106R-002718
12.4 - 28	STANDARD	94036417	R1	120 A8	8	W 11	W 9 ; W 10	12.4	50.2	23.4	147.6	TT	E11-106R-003551
16.9 - 30	HD	94028276	R1	132 A8	8	W 15 L	W 14 L	16.9	58.5	26.7	175.4	TT	E11-106R-004470
16.9 - 30	SPECIAL	94048755	R1	140 A8	12	W 15 L	W 14 L	16.9	58.5	27	178.1	TL	
16.9 - 30	SPECIAL	94004225	R1	132 A8	8	W 15 L	W 14 L	16.9	58.5	26.7	175.4	TT	E11-106R-004470
16.9 - 30	SPECIAL	94004232	R1	140 A8	12	W 15 L	W 14 L	16.9	58.5	27	178.1	TT	E11-106R-003010
16.9 - 30 (14 - 30)	STANDARD	94044108	R1	143 A8	14	W 15 L	W 14 L	16.9	58.5	26.7	175.4	TT	E11-106R-005243
16.9 - 30	STANDARD	94004188	R1	132 A8	8	W 15 L	W 14 L	16.9	58.5	26.7	175.4	TT	E11-106R-003441
16.9 - 30	STANDARD	94004195	R1	136 A8	10	W 15 L	W 14 L	16.9	58.5	26.7	175.4	TT	E11-106R-004472
16.9 - 30	STANDARD	94004201	R1	140 A8	12	W 15 L	W 14 L	16.9	58.5	27	178.1	TT	
18.4 - 30	HD	94029259	R1	135 A8	8	W 16 L	W 15 L	18.4	61	28	185.8	TT	E11-106R-004435
18.4 - 30	HD	94029129	R1	145 A8	12	W 16 L	W 15 L	18.4	61	28	185.8	TT	E11-106R-004475
18.4 - 30	HD	94004133	R1	147 A8	14	W 16 L	W 15 L	18.4	61	28	185.8	TT	E11-106R-003615
18.4 - 30	SPECIAL	94004300	R1	145 A8	12	W 16 L	W 15 L	18.4	61	28	185.8	TT	E11-106R-004436
18.4 - 30	STANDARD	94027514	R1	135 A8	8	W 16 L	W 15 L	18.4	61	28	185.8	TT	E11-106R-004473

Printed on 12/10/2023 9:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..