

## TR 137 - Teknik Özellikler



### Description

TR 137, BKT'nin, tüm hasat operasyonlarına en uygun lastiğidir. Yüksek yüklerde bile tarlalarda mükemmel çekiş sağlar. Lastik farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon daha iyi delinme direnci ve bu uygulamanın tüm tipik hasarlarına karşı koruma sağlar; "HD" versiyonu olağanüstü kesilme ve kopma direnci ve daha uzun lastik ömrü sunar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Biçerdöver

Version	STANDARD
Type	TL
Tyre Size	24.5 - 32
LI/SS	159 A8

## Dimensions US Standard

Usa code	94004324
Ply Rating	14
Section Width (inch)	24.5
Overall Diameter (inch)	71.1
Static Loaded Radius (inch)	31.8
Rolling Circumference (inch)	210.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-002273
TRA Code	R1

## Load capacity (lbs)

mph / psi	28
25	9650

Printed on 4/26/2024 10:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..