

TR 137 - Teknik Özellikler



Description

TR 137, BKT'nin, tüm hasat operasyonlarına en uygun lastiğidir. Yüksek yüklerde bile tarlalarda mükemmel çekiş sağlar. Lastik farklı versiyonlarda sunulmaktadır: "aramid kuşaklı" versiyon daha iyi delinme direnci ve bu uygulamanın tüm tipik hasarlarına karşı koruma sağlar; "HD" versiyonu olağanüstü kesilme ve kopma direnci ve daha uzun lastik ömrü sunar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Biçerdöver

Version	HD
Type	TL
Tyre Size	30.5L - 32
LI/SS	170 A6

Dimensions International Standard

Ply Rating	18
Section Width (mm)	770
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	831
Rolling Circumference (mm)	5520
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002283
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.10
30	6000

Printed on 4/26/2024 12:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..