

## TR 138 - Teknik Özellikler



### Description

TR 138, tarımda teleskopik yükleyiciler ve bekoloderler için özellikle tasarlanmıştır. Toprak işleme ilaçlama uygulamaları için uygundur. Yumuşak toprakta mükemmel çekiş, üstün kendi kendini temizleme özellikleri ve sabitleme, TR 138 lastiği zorlu zemin koşullarında bile ideal bir ortak kılan temel özelliklerdir.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Zirai: Bekoloder • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	17.5L - 24
LI/SS	151 A8

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	450
<b>Overall Diameter (mm)</b>	1290
<b>Static Loaded Radius (mm)</b>	576
<b>Rolling Circumference (mm)</b>	3836
<b>Rim Rec</b>	DW 15L
<b>Rim Alt</b>	DW 14L
<b>ECE</b>	E11-106R-005232

## Load capacity (Kg)

<b>km/h / bar</b>	<b>40</b>
<b>2.6</b>	<b>3450</b>

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/20/2025 3:05 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..