

TR 145 - Teknik Özellikler



Description

TR 145 özellikle küçük traktörler için tasarlanmıştır. Özel sırt deseni mükemmel çekiş ve olağanüstü kendi kendini temizleme özellikleri sağlar. Geniş ve derin pabuç tasarımı, lastiğin kullanma süresini uzatır. TR 145 lastiği, mükemmel sürüş konforu ve yüksek yön stabilitesi sunan geniş bir temas alanına sahiptir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Küçük Traktör

Version	STANDARD
Type	TT
Tyre Size	160/90 - 12
LI/SS	76 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	160
Overall Diameter (mm)	631
Static Loaded Radius (mm)	294
Rolling Circumference (mm)	1969
Rim Rec	4.00
ECE	E11-106R-005854
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	400

Printed on 4/18/2024 2:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..