

TR 171 - Teknik Özellikler



Description

TR 171, toprak işleme operasyonlarında kullanılan traktörler için uygun, derin sırtlı bir lastiktir. Olağanüstü kendini temizleme özellikleri sayesinde ıslak ve nemli topraklar için idealdir. Özel bir hamurla tasarlanan TR 171, en zorlu çalışma koşullarında bile mükemmel çekiş ve olağanüstü dayanıklılık sağlar.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	14.9 - 24
LI/SS	124 A8

Dimensions US Standard

Usa code	94028351
Ply Rating	8
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.3
Rim Rec	W 13
Rim Alt	W 11 ; W 12
ECE	E4-106R-002742
TRA Code	R1W+

Load capacity (lbs)

mph / psi	26
25	3520

Printed on 4/17/2024 11:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..