

TR 270 - Teknik Özellikler



Description

TR 270 toprak işleme uygulamaları için uygun bir traktör lastiğidir. Islak ve nemli toprakta maksimum performans sunmak için özel olarak tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 270 bu nitelikleri eksiksiz şekilde karşılar.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Traktör

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 23.1 - 26 |
| LI/SS | 149 A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94038503 |
| Ply Rating | 12 |
| Section Width (inch) | 23.2 |
| Overall Diameter (inch) | 64.8 |
| Static Loaded Radius (inch) | 29.1 |
| Rolling Circumference (inch) | 193.8 |
| Rim Rec | DW 20 A ; DW 20 B |
| ECE | E11-106R-004499 |
| TRA Code | R2 |

Load capacity (lbs)

| mph / psi | 24 |
|-----------|------|
| 25 | 7150 |

Printed on 4/18/2024 7:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..