

## TR 273 - Teknik Özellikler



### Description

TR 273 özellikle toprak işleme için uygun bir traktör lastiğidir ve ıslak ve nemli toprak üzerinde maksimum performans sağlamak üzere tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 273 bu nitelikleri eksiksiz şekilde karşılar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	143 A6

## Dimensions International Standard

Ply Rating	12
TKPH	1
Section Width (mm)	435
Overall Diameter (mm)	1530
Static Loaded Radius (mm)	706
Rolling Circumference (mm)	4800
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-005315
TRA Code	R2

## Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 4/20/2024 12:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..