

TR 273 - Teknik Özellikler



Description

TR 273 özellikle toprak işleme için uygun bir traktör lastiğidir ve ıslak ve nemli toprak üzerinde maksimum performans sağlamak üzere tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 273 bu nitelikleri eksiksiz şekilde karşılar.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	147 A8

Dimensions US Standard

Usa code	94045716
Ply Rating	10
Section Width (inch)	23.2
Overall Diameter (inch)	68.8
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	210.9
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003622
TRA Code	R2

Load capacity (lbs)

mph / psi	20
25	6800

Printed on 4/20/2024 12:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..