

TR 273 - Teknik Özellikler



Description

TR 273 özellikle toprak işleme için uygun bir traktör lastiğidir ve ıslak ve nemli toprak üzerinde maksimum performans sağlamak üzere tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 273 bu nitelikleri eksiksiz şekilde karşılar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	157 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	590
Overall Diameter (mm)	1748
Static Loaded Radius (mm)	794
Rolling Circumference (mm)	5356
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003645
TRA Code	R2

Load capacity (Kg)

km/h / bar	1.90
30	4125

Printed on 4/19/2024 6:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..