

TR 273 - Veri Sayfasını İndir



Description

TR 273 özellikle toprak işleme için uygun bir traktör lastiğidir ve ıslak ve nemli toprak üzerinde maksimum performans sağlamak üzere tasarlanmıştır. Bu toprak koşullarında, bir lastiğin üstün tutuş ve gelişmiş kendini temizleme özellikleri sunması gereklidir. TR 273 bu nitelikleri eksiksiz şekilde karşılar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Traktör

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | TKPH | ECE |
|-----------|----------|----------|--------|----|-------------------|-----------------|-----|------|-----|------|------|------|-----------------|
| 12.4 - 24 | STANDARD | R2 | 121 A6 | 8 | W 11 | W 10 | 315 | 1195 | 550 | 3722 | TT | 0 | E11-106R-004100 |
| 13.6 - 24 | STANDARD | R2 | 123 A6 | 8 | W 12 | W 11 | 350 | 1240 | 570 | 3795 | TT | 1 | E11-106R-005252 |
| 14.9 - 24 | STANDARD | R2 | 128 A6 | 8 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | TT | | E11-106R-004514 |
| 14.9 - 24 | STANDARD | R2 | 132 A6 | 10 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | TT | | E11-106R-004515 |
| 18.4 - 26 | STANDARD | R2 | 146 A6 | 12 | W 16 | W 15 | 470 | 1490 | 673 | 4534 | TT | 1 | E11-106R-005314 |
| 23.1 - 26 | STANDARD | R2 | 156 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-004628 |
| 23.1 - 26 | STANDARD | R2 | 149 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-003620 |
| 23.1 - 26 | STANDARD | R2 | 153 A6 | 12 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-003395 |
| 14.9 - 28 | STANDARD | R2 | 130 A6 | 8 | W 13 | W 12 | 385 | 1410 | 651 | 4368 | TT | | E11-106R-004516 |
| 16.9 - 30 | STANDARD | R2 | 143 A6 | 12 | W 15 L | W 14 L | 435 | 1530 | 706 | 4800 | TT | 1 | E11-106R-005315 |
| 18.4 - 30 | STANDARD | R2 | 149 A6 | 12 | W 16 L | W 15 L | 465 | 1585 | 723 | 4924 | TT | | E11-106R-003621 |
| 23.1 - 30 | STANDARD | R2 | 157 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1748 | 794 | 5356 | TT | 0 | E11-106R-003645 |
| 23.1 - 30 | STANDARD | R2 | 151 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1748 | 794 | 5356 | TT | | E11-106R-003622 |
| 18.4 - 34 | STANDARD | R2 | 150 A6 | 12 | DW 16A | W16L,W15L,DW15L | 475 | 1701 | 775 | 5253 | TT | | E11-106R-004517 |
| 23.1 - 34 | STANDARD | R2 | 160 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1850 | 833 | 5634 | TT | 1 | E11-106R-003646 |
| 23.1 - 34 | STANDARD | R2 | 153 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1850 | 833 | 5634 | TT | | E11-106R-003623 |
| 18.4 - 38 | STANDARD | R2 | 152 A6 | 12 | W 16 | W 15 | 465 | 1800 | 822 | 5579 | TT | 1 | E11-106R-005316 |

Printed on 4/19/2024 11:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..