

## TR 315 - Teknik Özellikler



### Description

TR 315; çim ve bahçe, toprak işleme ve belediye operasyonları için uygundur. Uygulamalı makine, hendek kazıcı ve meyve hasadı makineleri için idealdir. TR 315 lastik; her koşulda olağanüstü sabitleme, müthiş kendi kendini temizleme özellikleri ve mükemmel kavrama sağlayan geniş bir temas alanına sahiptir.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Zirai: Uygulamalı makine • Meyve hasadı makinesi •  
Hendek kazıcı

Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	390
Overall Diameter (mm)	800
Static Loaded Radius (mm)	354
Rolling Circumference (mm)	2320
Rim Rec	13 LB
ECE	E4-106R-002208

## Load capacity (Kg)

km/h / bar	3.10
50	1250

Printed on 4/20/2024 12:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..