

## TR 317 - Teknik Özellikler



### Description

TR 317; uygulamalı makine, hendek kazıcı ve meyve hasadı makineleri ile belediye ve toprak işleme operasyonlarına uygun bir lastiktir. TR 317 lastik; mükemmel kendi kendini temizleme özellikleri ile birlikte her koşulda olağanüstü sabitleme ve mükemmel kavrama sağlayan geniş bir temas alanına sahiptir.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Uygulamalı makine • Meyve hasadı makinesi •  
Hendek kazıcı

|           |               |
|-----------|---------------|
| Version   | HD            |
| Type      | TL            |
| Tyre Size | 18 X 8.50 - 8 |

## Dimensions International Standard

|                            |                               |
|----------------------------|-------------------------------|
| Ply Rating                 | 6                             |
| Section Width (mm)         | 215                           |
| Overall Diameter (mm)      | 450                           |
| Static Loaded Radius (mm)  | 198                           |
| Rolling Circumference (mm) | 1305                          |
| Rim Rec                    | 7.00 I - 55 ; I - 70 ; I - 90 |

## Load capacity (Kg)

| km/h / bar | 2.30 |
|------------|------|
| 15         | 475  |

Printed on 4/25/2024 3:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..