

TR 318 - Teknik Özellikler

Description

TR 318 özellikle ilaçlama araçları ve uygulamalı makineler için tasarlanmıştır. Çift açılı dişleri mükemmel çekiş ve olağanüstü sürüş konforu sağlar. TR 318 ayrıca olağanüstü kendi kendini temizleme özelliklerine sahiptir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • İlaçlama



Version	STANDARD
Type	TT
Tyre Size	26 X 10.00 - 12
LI/SS	107 A3

Dimensions International Standard

Ply Rating	8
Section Width (mm)	265
Overall Diameter (mm)	675
Rim Rec	8.5
ECE	E11-106R-004522

Load capacity (Kg)

km/h / bar	3.70
15	975

Printed on 2/22/2024 9:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..