

TR 319 - Teknik Özellikler



Description

TR 319; çim ve bahçe, belediye ve toprak işleme uygulamalarında kullanılan uygulamalı makine, meyve hasadı makinesi ve hendek kazıcılara yönelik bir lastiktir. En iyi çekişi sağlayan geniş bir temas alanına sahip olan TR 319, sabitleme ve kendi kendini temizleme özelliklerinin gerekli olduğu ıslak yüzeylerdeki uygulamalar için çok uygundur.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Meyve hasadı makinesi •
Hendek kazıcı

Version	STANDARD
Type	TL
Tyre Size	29 X 12.50 - 15
LI/SS	98 B

Dimensions International Standard

Ply Rating	6
Section Width (mm)	312
Overall Diameter (mm)	755
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2264
Rim Rec	10 LB
ECE	E11-106R-004604

Load capacity (Kg)

km/h / bar	2.10
50	750

Printed on 4/17/2024 5:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..