

TR 319 - Teknik Özellikler



Description

TR 319; çim ve bahçe, belediye ve toprak işleme uygulamalarında kullanılan uygulamalı makine, meyve hasadı makinesi ve hendek kazıcılara yönelik bir lastiktir. En iyi çekişi sağlayan geniş bir temas alanına sahip olan TR 319, sabitleme ve kendi kendini temizleme özelliklerinin gerekli olduğu ıslak yüzeylerdeki uygulamalar için çok uygundur.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Meyve hasadı makinesi •
Hendek kazıcı

Version	STANDARD
Type	TL
Tyre Size	29 X 12.50 - 15
LI/SS	98 B

Dimensions US Standard

Usa code	94051601
Ply Rating	6
Section Width (inch)	12.3
Overall Diameter (inch)	29.7
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	89.1
Rim Rec	10 LB
ECE	E11-106R-004604

Load capacity (lbs)

mph / psi	30
30	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 10:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..