TR 387 IND - Teknik Özellikler

Description

TR 387 IND, endüstriyel römorklar ve kompaktörler için uygun endüstriyel bir lastiktir. Yüksek yük kapasitesi sağlar, ayrıca kesik ve kopma direnci, ağır hizmetler ve dayanıklılık bakımından özel kullanıcı gereksinimlerini karşılamak için farklı modellerde mevcuttur. "Çift damak telli" modeli özellikle endüstriyel traktörler ve römork kullanılarak yapılan taşımacılık operasyonları için uygundur.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Kompaktör • Traktör • Römork

Version	DUAL BEAD HD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	164 A6

Dimensions International Standard

Ply Rating	18
Section Width (mm)	605
Overall Diameter (mm)	1675
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

Load capacity (Kg)

km/h / bar	2.60
30	5000

Printed on 4/23/2024 8:58 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..