

TR 387 - Teknik Özellikler



Description

TR 387, şeker kamışı römorkları ve kompaktörler için uygun bir tarımsal sanayi lastiğidir. Daha uzun bir kullanım ömrüyle birlikte olağanüstü yüksek yük kapasitesine sahiptir ve kesilme ve kopma direnci, ağır hizmetler ve dayanıklılık açısından belirli kullanıcı gerekliliklerini karşılayan farklı versiyonlarda sunulmaktadır. "Çift damaklı" versiyon, römorklar kullanılan endüstriyel traktörler ve taşıma operasyonları için özellikle uygundur.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Römork

Endüstriyel: Kompaktör

Version	DUAL BEAD HD
Type	TL
Tyre Size	620/75 - 30 (23.1 - 30)
LI/SS	160 A8

Dimensions US Standard

Usa code	94052868
Ply Rating	18
Section Width (inch)	23.8
Overall Diameter (inch)	65.9
Rim Rec	DW 20 A ; DW 20 B
TRA Code	R3

Load capacity (lbs)

mph / psi	38
25	11000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/05/2025 02:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..