

## TR 390 IND - Teknik Özellikler



### Description

TR 390 IND, endüstriyel römorklar ve kompaktörler için uygun endüstriyel bir lastiktir. Yüksek yük kapasitesi sağlar, ayrıca kesik ve kopma direnci, ağır hizmetler ve dayanıklılık bakımından özel kullanıcı gereksinimlerini karşılamak için farklı modellerde mevcuttur. "Çift damak telli" modeli özellikle endüstriyel traktörler ve römork kullanılarak yapılan taşımacılık operasyonları için uygundur.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Endüstriyel: Kompaktör • Traktör • Römork

Version	DUAL BEAD HD
Type	TL
Tyre Size	28L - 26
LI/SS	172 A6

## Dimensions International Standard

Ply Rating	20
Section Width (mm)	714
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4545
Rim Rec	DW 25 B
Rim Alt	DW 23 B
TRA Code	R3

## Load capacity (Kg)

km/h / bar	2.80
30	6300

Printed on 4/26/2024 7:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..