

## TR 390 IND - Teknik Özellikler



### Description

TR 390 IND, endüstriyel römorklar ve kompaktörler için uygun endüstriyel bir lastiktir. Yüksek yük kapasitesi sağlar, ayrıca kesik ve kopma direnci, ağır hizmetler ve dayanıklılık bakımından özel kullanıcı gereksinimlerini karşılamak için farklı modellerde mevcuttur. "Çift damak telli" modeli özellikle endüstriyel traktörler ve römork kullanılarak yapılan taşımacılık operasyonları için uygundur.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Endüstriyel: Kompaktör • Traktör • Römork

Version	DUAL BEAD HD
Type	TL
Tyre Size	28L - 26
LI/SS	168 A8

## Dimensions US Standard

Usa code	94065349
Ply Rating	20
Section Width (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
TRA Code	R3

## Load capacity (lbs)

mph / psi	42
25	12350

Printed on 12/3/2023 6:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..