

TR 390 - Teknik Özellikler



Description

TR 390, şeker kamışı römorkları ve kompaktörler için uygun bir tarımsal sanayi lastiğidir. TR 390 olağanüstü yüksek yük kapasitesi ve artan dayanıklılık sunar. "Çift damaklı HD" versiyon, römorklar kullanılan endüstriyel traktörler ve taşıma operasyonları için özellikle uygunken "çift damaklı HD özel" versiyon ağır hizmetler için idealdir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Römork

Endüstriyel: Kompaktör

| | |
|-----------|--------------|
| Version | DUAL BEAD HD |
| Type | TL |
| Tyre Size | 23.1 - 26 |
| LI/SS | 157 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94030675 |
| Ply Rating | 18 |
| Section Width (inch) | 23.4 |
| Overall Diameter (inch) | 61.4 |
| Static Loaded Radius (inch) | 27.2 |
| Rolling Circumference (inch) | 178.9 |
| Rim Rec | DW 20 B |
| ECE | E11-106R-004607 |
| TRA Code | R3 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 38 |
| 25 | 9090 |

Printed on 2/21/2024 6:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..