

TR 459 - Teknik Özellikler



Description

TR 459 traktörlerle ve bekoloderle yapılan belediye ve bakım uygulamalarıyla birlikte özellikle kazma ve yükleme operasyonları için tasarlanmıştır. Yüksek sabitleme sunar, ayrıca iki versiyonu mevcuttur. "Özel" versiyon lastik kullanım ömrünü uzatır.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Bekoloder • Traktör

Endüstriyel: Bekoloder

Version	INDUSTRIAL
Type	TL
Tyre Size	17.5L - 24
LI/SS	148 A8

Dimensions US Standard

Usa code	94016594
Ply Rating	12
Section Width (inch)	17.5
Overall Diameter (inch)	50
Static Loaded Radius (inch)	21.9
Rolling Circumference (inch)	150.6
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-004659
TRA Code	R4

Load capacity (lbs)

mph / psi	40
25	6950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 1:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..