

TR 461 - Teknik Özellikler



Description

TR 461 traktörlerle yapılan şehircilik ve bakım uygulamaları için olduğu kadar, teleskopik taşıyıcılarla yapılan yükleme çalışmaları için de uygun bir BKT desenine sahiptir. Yanak koruması kesilmelere ve zedelenmelere karşı özel dayanıklılık sunarak, kusursuz istikrarın yanı sıra sert yüzeylerde daha uzun ömür sağlar.

UM

International Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder • Teleskopik yükleyici • Traktör

Version	STANDARD
Type	TL
Tyre Size	16.9 - 24
LI/SS	151 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	440
Overall Diameter (mm)	1280
Static Loaded Radius (mm)	566
Rolling Circumference (mm)	3763
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.90
40	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 8:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..