

TR 461 - Teknik Özellikler



Description

TR 461 traktörlerle yapılan şehircilik ve bakım uygulamaları için olduğu kadar, teleskopik taşıyıcılarla yapılan yükleme çalışmaları için de uygun bir BKT desene sahiptir. Yanak koruması kesilmelere ve zedelenmelere karşı özel dayanıklılık sunarak, kusursuz istikrarın yanı sıra sert yüzeylerde daha uzun ömür sağlar.

UM

US Standard

Construction

 BIAS

Machinery

Endüstriyel: Bekoloder • Teleskopik yükleyici • Traktör

Version	STANDARD
Type	TL
Tyre Size	21L - 24
LI/SS	157 A8

Dimensions US Standard

Usa code	94016785
Ply Rating	14
Section Width (inch)	21.3
Overall Diameter (inch)	54.5
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	160.3
Rim Rec	DW 18 L
TRA Code	R4

Load capacity (lbs)

mph / psi	36
25	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/15/2024 3:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..