



## TR 461 - Veri Sayfasını İndir



### Description

TR 461 traktörlerle yapılan şehircilik ve bakım uygulamaları için olduğu kadar, teleskopik taşıyıcılarla yapılan yükleme çalışmaları için de uygun bir BKT desenine sahiptir. Yanak koruması kesilmelere ve zedelenmelere karşı özel dayanıklılık sunarak, kusursuz istikrarın yanı sıra sert yüzeylerde daha uzun ömür sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Bekoloder • Teleskopik yükleyici • Traktör

SIZE	Version	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.5/80 - 18	STANDARD	R4		138 A8	150 A8	18	W 9	11	305	987	435	2902	TL	E11-106R-006914
12.5/80 - 18	STANDARD	R4		129 A8	142 A8	12	W 9	11	305	987	435	2902	TL	E11-106R-005367
16.9 - 24	STANDARD	R4	151 A8			14	DW 15 L	DW 14 L	440	1280	566	3763	TL	
19.5L - 24	STANDARD	R4	151 A8			12	DW 16 L		490	1310	578	3851	TL	
19.5L - 24	STANDARD	R4	154 A8			14	DW 16 L		490	1310	578	3851	TL	
21L - 24	STANDARD	R4	157 A8			14	DW 18 L		540	1385	607	4072	TL	
16.9 - 28	STANDARD	R4	154 A8			14	DW 15 L	DW 14 L	440	1390	620	4087	TL	
620/60 B 34	HD	R4	175 A8				DW 20 B		615	1629	750	4930	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/15/2024 1:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..