



TR 675 - Veri Sayfasını İndir



Description

TR 675 özellikle orman uygulamaları için tasarlanmış çift yönlü bir lastiktir. Sağlam dış tasarımı mükemmel çekiş ve kendi kendini temizleme özelliği sağlarken güçlü gövde yapısı yüksek yüklerin taşınmasına izin verir ve çelik kuşakları lastiği delinmelere ve hasarlara karşı korur. TR 675, zorlu koşullar altındaki arazilerde bile mükemmel kesik ve kopma direnci sağlayan kesilmeye karşı dirençli bir sırt hamuruna sahiptir.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Yükleyici taşıyıcı

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
540/65 - 28	STEEL BELTED	94059959	LS2	155 A8/161 A2	16	W 16 L	W 18 L	20.9	56.1	26.1	174.8	TL	E11-106R-005271

Printed on 4/17/2024 5:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..