

TR 678 - Veri Sayfasını İndir



Description

TR 678 özellikle orman uygulamaları için tasarlanmıştır. Sağlam dış tasarımı mükemmel çekiş ve kendi kendini temizleme özelliği sağlar. Güçlü gövde yapısı sayesinde yüksek yük kapasitesine sahiptir ve çelik kuşakları lastiği delinmelere ve hasarlara karşı korur. TR 678 zorlu koşullar altındaki arazilerde bile mükemmel kesik ve kopma direnci sağlayan kesilmeye karşı dirençli bir sırt hamuruna sahiptir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork
Endüstriyel: Ekskavatör • Römork

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
600/55 - 26.5	STEEL BELTED	LS2	172 A2 / 165 A8	20	AG 20.00		605	1350			TL	E11-106R-008132
780/50 - 28.5	STEEL BELTED	LS2	190 A2/ 182 A8	24	AG 26.00		770	1515			TL	E11-106R-006975
600/65 - 34	STEEL BELTED	LS2	166 A2 / 162 A6	16	DW 20 B		610	1644	758	4916	TL	
600/65 - 34	STEEL BELTED	LS2	170 A2 / 166 A6	20	DW 20 B		610	1644	758	4916	TL	
600/65 - 34	STEEL BELTED	LS2	164 A2/160 A6	14	DW 20 B		610	1644	758	4916	TL	E11-106R-003648
710/55 - 34	STEEL BELTED	LS2	173 A2/ 168 A6	20	DW 24 B		700	1640	757	4890	TL	
710/55 - 34	STEEL BELTED	LS2	168 A2/163 A6	14	DW 24 B		700	1640	757	4890	TL	E11-106R-007156

Printed on 4/27/2024 12:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..