

TR 882 - Teknik Özellikler



Description

TR 882, çeşitli uygulamalar ve araçlar için çok yönlü bir lastiktir. Uygulamalı makine, saman hasadı makinesi/balyalama makinesi ve şeker kamışı makinesine uyacak şekilde tasarlanmıştır. Hasarı azaltmak için özel bir hamurla tasarlanan bu lastik, her arazi koşulunda mükemmel dayanıklılık ve çekişe sahiptir. TR 882'nin, ayrıca belirli son kullanıcı gereksinimlerini karşılamak için "aramid kuşaklı", "HD" ve "özel" versiyonları da mevcuttur.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Uygulamalı makine • Römork
Endüstriyel: Römork

Version	ARAMID BELTED HD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	400
Overall Diameter (mm)	875
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2605
SRI (mm)	410
Rim Rec	AG 13.00
ECE	E11-106R-005354

Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250
10 DW	3220
25 DW	2735
30 DW	2575
40 DW	2300

Printed on 4/27/2024 4:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..