TRAC FARM PLUS - Teknik Özellikler

Description

TRAC FARM PLUS, toprak işleme ve taşıma uygulamaları için özel olarak tasarlanmış bir arka kamyon lastiğidir. Lastik, hem mükemmel çekiş hem de yolda rahat bir sürüş sağlamak için çift açılı dişlere sahip daha derin bir lastik sırtı sunar. Özel sırt tasarımı, mükemmel kendi kendini temizleme özellikleri ve daha iyi sabitleme için daha fazla temas sağlar. TRAC FARM PLUS daha uzun lastik kullanım ömrü sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	125 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	320
Overall Diameter (mm)	1295
Static Loaded Radius (mm)	603
Rolling Circumference (mm)	3899
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004526
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	1650

Printed on 4/25/2024 11:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..