



# TRAC FARM PLUS - Teknik Özellikler



## Description

TRAC FARM PLUS, toprak işleme ve taşıma uygulamaları için özel olarak tasarlanmış bir arka kamyon lastiğiidir. Lastik, hem mükemmel çekiş hem de yolda rahat bir sürüş sağlamak için çift açılı dışlere sahip daha derin bir lastik sırtı sunar. Özel sırt tasarıımı, mükemmel kendi kendini temizleme özellikleri ve daha iyi sabitleme için daha fazla temas sağlar. TRAC FARM PLUS daha uzun lastik kullanım ömrü sağlar.

## UM

US Standard

## Construction

❖ BIAS

## Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	121 A8

## Dimensions US Standard

Usa code	94045419
Ply Rating	12
Section Width (inch)	12.6
Overall Diameter (inch)	51
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	153.5
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004526
TRA Code	R1

## Load capacity (lbs)

mph / psi	36
25	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 10:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..