

## TRAC FARM - Teknik Özellikler



### Description

TRAC FARM, toprak işleme ve taşıma uygulamalarında kullanılan traktörler için özel olarak tasarlanmış ağır hizmet tipi bir lastiktir. Derin sırtı ve özel kesilme ve kopmaya karşı dirençli hamuru, lastiği en zorlu çalışma koşullarına uygun hale getirerek tüm ürün kullanım ömrü boyunca en iyi yatırım getirisini sağlar. TRAC FARM, daha fazla pabuca sahiptir ve olağanüstü çekiş ile kendi kendini temizleme özellikleri sağlar.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	13.6 - 28
LI/SS	128 A6

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	365
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	625
Rolling Circumference (mm)	4034
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003572
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.30
30	1800

Printed on 4/24/2024 6:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..