

## TRAC GRADER + - Teknik Özellikler



### Description

TRAC GRADER + (G-2) greyderler için konvansiyonel bir lastiktir. Bütçesine öncelik veren müşteriler için kusursuz seçimdir. Sağlam gövdesi uzun süre dayanıklılık için tasarlanmıştır. Kendini temizleyen diş deseni, tüm koşullarda en iyi çekiş gücünü sağlayan açık çekme-boşluk oranına sahiptir. "Özel" modeli, kesilme ve parçalanmaya karşı dayanıklı özel bileşikten üretilmiştir.

### UM

US Standard

### Construction

BIAS

### Machinery

Yoldışı: Greyder

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

## Dimensions US Standard

Usa code	94014545
Ply Rating	12
Overall Width (inch)	13.4
Overall Diameter (inch)	50.4
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	155.2
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
ECE	E11-106R-003629
TRA Code	G2

## Load capacity (lbs)

mph / psi	44
25	6000

Printed on 4/20/2024 9:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..