

TRAC GRADER + - Teknik Özellikler



Description

TRAC GRADER + (G-2) greyderler için konvansiyonel bir lastiktir. Bütçesine öncelik veren müşteriler için kusursuz seçimdir. Sağlam gövdesi uzun süre dayanıklılık için tasarlanmıştır. Kendini temizleyen diş deseni, tüm koşullarda en iyi çekiş gücünü sağlayan açık çekme-boşluk oranına sahiptir. "Özel" modeli, kesilme ve parçalanmaya karşı dayanıklı özel bileşikten üretilmiştir.

UM

US Standard

Construction

 BIAS

Machinery

Yoldışı: Greyder

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 13.00 - 24 |

Dimensions US Standard

| | |
|------------------------------|------------------------------|
| Usa code | 94014569 |
| Ply Rating | 14 |
| Overall Width (inch) | 13.4 |
| Overall Diameter (inch) | 50.4 |
| Static Loaded Radius (inch) | 23.6 |
| Rolling Circumference (inch) | 155.2 |
| Rim Rec | 8.00 TG SDC |
| Rim Alt | 9.00/1.5 (DC) ; 10.00/VA SDC |
| ECE | E11-106R-003630 |
| TRA Code | G2 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 51 |
| 25 | 6600 |

Printed on 4/21/2024 1:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..