

TRAC GRADER + - Teknik Özellikler



Description

TRAC GRADER + (G-2) greyderler için konvansiyonel bir lastiktir. Bütçesine öncelik veren müşteriler için kusursuz seçimdir. Sağlam gövdesi uzun süre dayanıklılık için tasarlanmıştır. Kendini temizleyen diş deseni, tüm koşullarda en iyi çekiş gücünü sağlayan açık çekme-boşluk oranına sahiptir. "Özel" modeli, kesilme ve parçalanmaya karşı dayanıklı özel bileşikten üretilmiştir.

UM

International Standard

Construction

 BIAS

Machinery

Yoldışı: Greyder

Version SPECIAL

Type TL

Tyre Size 14.00 - 24

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	364
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	598
Rolling Circumference (mm)	3990
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC; 10.00 WA SDC
TRA Code	G2

Load capacity (Kg)

km/h / bar	2.50
40	3075

Printed on 4/20/2024 9:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..