

TRAC MASTER - Teknik Özellikler

Description

TRAC MASTER, küçük traktörler ve uygulamalı makineler için uygun bir toprak işleme ve çim ve bahçe lastiğidir. Sırt tasarımı, arazide mükemmel çekiş ve optimum kendi kendini temizleme özellikleri ile birlikte mükemmel arazi koruması sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Küçük Traktör



Version	STANDARD
Type	TL
Tyre Size	31 X 15.50 - 15

Dimensions International Standard

Ply Rating	6
Section Width (mm)	405
Overall Diameter (mm)	792
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2372
Rim Rec	13 LB
ECE	E4-106R-002209

Load capacity (Kg)

km/h / bar	2.10
50	975

Printed on 4/26/2024 9:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..