

TRAC SUPER - Teknik Özellikler

Description

TRAC SUPER, BKT'nin belediye segmentinde tanıtılan ilk radyal lastiktir. Çelik kuşaklı lastik yapısı, en iyi çekiş performansı ile mükemmel, sorunsuz bir sürüş sağlar. Sonuç olarak, özellikle, parklar ve yol kenarları gibi geniş çim yüzeylerindeki uygulamalar için uygundur.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Küçük Traktör



Version	STANDARD
Type	TL
Tyre Size	400/50 R 15
LI/SS	118 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	775
Static Loaded Radius (mm)	329
Rolling Circumference (mm)	2269
SRI (mm)	370
Rim Rec	13.00
ECE	E11-106R-009073

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6
50	845	1085	1320
40	845	1085	1320
30	950	1215	1480
20	1070	1370	1665
10	1185	1520	1850

Printed on 4/19/2024 4:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..