

## TUF LUG - Teknik Özellikler

### Description

TUF LUG, taşıma uygulamalarında kullanılan römork ve kamyonetler için uygundur. Bu lastik, iyi bir çekiş ve mükemmel dayanıklılık sunar ve uzun bir kullanım ömrü sağlar.

### UM

US Standard

### Construction

 BIAS

### Machinery

Zirai: Kamyonet • Römork

Endüstriyel: Kamyonet • Römork

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

### Dimensions US Standard

Usa code	94014323
Ply Rating	16
Section Width (inch)	8.5
Overall Diameter (inch)	32.7
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (lbs)

mph / psi	110
62 LS	3530
62 LD	3085

Printed on 5/8/2024 1:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..