

V-FLEXA - Teknik Özellikler



Description

V-FLEXA, tarım römorkları için özel olarak tasarlanmış bir radyal lastiktir. Son nesil yayılma özelliği bulunan ürün, ağır yüklerin hem arazide hem yolda, aynı ebattaki standart bir lastikten %30 daha düşük şişirme basıncıyla taşınmasını sağlayan VF teknolojisine sahiptir. İlave çelik kayışlar, gövdeye darbelere karşı büyük direnç sağlar. V-FLEXA sadece ağır yükleri tam güvenlikle desteklemekle kalmaz, aynı zamanda mükemmel ağırlık dağılımı sayesinde toprak sıkışmasını önler. Dahası, V-FLEXA mükemmel kendi kendini temizleme özellikleri, dayanıklılık ve düşük yuvarlanma direncine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Römork

| | |
|--------------------|------------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | VF 710/50 R 30.5 |
| LI/SS | 178 D |
| LI/SS DRIVE WHEEL | 178 D |
| LI/SS FREE ROLLING | 178 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 727 |
| Overall Diameter (mm) | 1485 |
| Static Loaded Radius (mm) | 654 |
| Rolling Circumference (mm) | 4511 |
| SRI (mm) | 700 |
| Rim Rec | AG 24.00 |
| ECE | E11-106R-008831 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|-------|-------|
| 70 | 2730 | 3485 | 4095 | 4780 | 5395 | 6145 | 6825 |
| 65 | 3000 | 3825 | 4500 | 5250 | 5925 | 6750 | 7500 |
| 50 | 3510 | 4480 | 5265 | 6145 | 6935 | 7900 | 8775 |
| 40 | 3870 | 4935 | 5805 | 6775 | 7645 | 8710 | 9675 |
| 10 | 4920 | 6275 | 7380 | 8610 | 9720 | 11070 | 12300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 9:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..