

V-FLEXA - Teknik Özellikler



Description

V-FLEXA, tarım römorkları için özel olarak tasarlanmış bir radyal lastiktir. Son nesil yayılma özelliği bulunan ürün, ağır yüklerin hem arazide hem yolda, aynı ebattaki standart bir lastikten %30 daha düşük şişirme basıncıyla taşınmasını sağlayan VF teknolojisine sahiptir. İlave çelik kayışlar, gövdeye darbelere karşı büyük direnç sağlar. V-FLEXA sadece ağır yükleri tam güvenlikle desteklemekle kalmaz, aynı zamanda mükemmel ağırlık dağılımı sayesinde toprak sıkışmasını önler. Dahası, V-FLEXA mükemmel kendi kendini temizleme özellikleri, dayanıklılık ve düşük yuvarlanma direncine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Römork

Version	STEEL BELTED
Type	TL
Tyre Size	VF 750/45 R 26.5
LI/SS	176 D
LI/SS DRIVE WHEEL	176 D
LI/SS FREE ROLLING	176 D

Dimensions International Standard

Section Width (mm)	755
Overall Diameter (mm)	1349
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	4095
SRI (mm)	650
Rim Rec	AG 24.00
ECE	E11-106R-008832

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2
70	2590	3300	3880	4530	5110	5820	6465
65	2840	3625	4260	4970	5610	6390	7100
50	3325	4240	4990	5820	6565	7480	8310
40	3665	4675	5500	6415	7240	8245	9160
10	4660	5940	6990	8155	9200	10485	11645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 8:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..