

VIJETA - Teknik Özellikler



Description

VIJETA hem yola yönelik hem de yol harici uygulamalar için uygun bir tarım lastiğidir. 5 düz dişli deseni yük dağılımını iyileştirir. Ek olarak, aşınmaya karşı dayanıklı bileşimi ve güçlü gövdesi uzun bir lastik ömrü boyunca sağlam kalır.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Römork

Version	STANDARD
Type	TT
Tyre Size	5.00 - 19
LI/SS	94 A3

Dimensions US Standard

Usa code	94052349
Ply Rating	6
Section Width (inch)	5.5
Overall Diameter (inch)	29.7
Rim Rec	3.00

Load capacity (lbs)

mph / psi	55
10	1480

Printed on 4/27/2024 9:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..