

## XL GRIP (ADT) - Teknik Özellikler



### Description

XL GRIP (ADT), benzersiz çekişin gerekli olduğu ağır şartlar altında kesilmeleri ve delinmeleri en aza indirmekte kullanılan Belden kırmalı kaya kamyonları için özel olarak tasarlanmış çapraz katlı bir lastiktir. Bu özellikler uzun lastik kullanım ömrü sağlar.

### UM

International Standard

### Construction

BIAS

### Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT)

Version	STANDARD
---------	----------

Type	TL
------	----

Tyre Size	26.5 - 25
-----------	-----------

## Dimensions International Standard

Ply Rating	32
Overall Width (mm)	680
Overall Diameter (mm)	1740
Static Loaded Radius (mm)	796
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
TRA Code	E3

## Load capacity (Kg)

km/h / bar	4.25
50	11200

Printed on 4/25/2024 10:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..