

## XL GRIP (ADT) - Teknik Özellikler



### Description

XL GRIP (ADT), benzersiz çekişin gerekli olduğu ağır şartlar altında kesilmeleri ve delinmeleri en aza indirmekte kullanılan Belden kırmalı kaya kamyonları için özel olarak tasarlanmış çapraz katlı bir lastiktir. Bu özellikler uzun lastik kullanım ömrü sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT)

Version	STANDARD
---------	----------

Type	TL
------	----

Tyre Size	26.5 - 25
-----------	-----------

## Dimensions US Standard

Usa code	94057870
Ply Rating	32
Overall Width (inch)	26.8
Overall Diameter (inch)	68.5
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	202.8
Rim Rec	22.00/3.0
TRA Code	E3

## Load capacity (lbs)

mph / psi	62
30	24690

Printed on 4/25/2024 9:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..